

BIRDWIRE

DATA SHEET



THE DISSUASIVE PROCESS FOR BIRDS REMOVAL

BIRDWIRE, dissuasive process for removal of birds. Very discreet, quick to instal, economical.

- No risk of injury, ideal for window sills, ballustrade...
- To prevent pigeons from setting on the ledges of buildings. Recommended for low bird pressure.

MAIN FEATURES:

- · High resistance to oxygen, ultraviolet, alkalisalts.
- · Very poor solvent resistence.
- · Perfectly maintained because fixed in the masonry

TECHNICAL DATAS EIRDWIRE:

- Nylon coated stainless steel cable :
 - Diameter : 0,70 mm
 - Lenght : 100 m
 - · Very good strength, which makes it very effective
 - Very good elasticity = Combined cable / hook effect
 - · Good resistance to salt spray

• Anchor rivets :

• Diameter : 6 mm





Diameter: 8 mm

• Lenght : 37 mm



• Diameter : 2 mm

• Lenght : 8 mm

· Stainless-steel rod:

• Diameter : 4 mm

• Height: 110 mm



BIRDWIRE BOX COMPOSITION:

• Stainless steel cable : 100 m roll

• Stainless-steel rod : Pack of 100 pcs • Gutter rods : Pack of 10 pcs

• Roof rods : Pack of 10 pcs

• Anchor rivets : Pack of 100 pcs

• Spring: Pack of 100 pcs

• Clamps : Pack of 100 pcs

ECOPIC® ADVICE:

- Caution : ask the architect for permission before drilling the support.
- The installer must ensure the seal after drilling the support.

Cleaning: For a better guarantee, clean with SELCLEANING®, (natural cleaner)

Guarantee: Refer to the conditions defined in our brochure or website

WHERE INSTALLING:

• All types of buildings, statues, museums, factories, schools, balconies, railings...

MANUAL:

See installation sheet

